



(Spring Rate R = 0.94 N/mm
 (Wire Length L = 13.2 mm)
 (Coil Pitch P = mm)
 (Mass m = 0.104 g)

Illustr. 1. Spring ends lined up and ground

Illustr. 2. Spring ends lined up

Illustr. 3. Spring ends lined up, forged and ground

| | | |
|---|------------------------------|--|
| 1 | No. of Active Coils | n = 8.5 |
| | Total No. of Coils | nt = 10.5 |
| 2 | Direction of Coils | right <input checked="" type="radio"/> left <input type="radio"/> |
| 3 | Deburring of Spring Ends | no <input checked="" type="radio"/> inside <input type="radio"/> outside <input type="radio"/> |
| 4 | Working Path (Stroke) | |
| 5 | Stress Cycle Frequency | |
| 6 | Range of working temperature | 0 .. 80 °C |
| 7 | Wire or Rod Surface | drawn <input checked="" type="radio"/> rolled <input type="radio"/> tipless grinding <input type="radio"/> spring shot-blasted with steel balls <input type="radio"/> |
| 8 | Surface Protection: | |
| 9 | Material: | SH/DH |

| | | | | | |
|----|---|-----------------------|-----------------------|-----------------------|----------------------------------|
| 10 | Permissible Deviations according to EN 15800 Quality Class | | | | DIN 2096 |
| | | 1 | 2 | 3 | |
| | De, Di | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| | L0 | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| | F1 | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| | F2 | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| | e1 | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| | e2 | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| | d | | | | |
| 11 | Manufacturing Tolerance | | | by: | |
| | a) if the spring force and the spring length are specified | | | L0 | <input type="radio"/> |
| | b) if the spring force, the spring length and L0 are specified | | | n and d | <input checked="" type="radio"/> |
| | | | | n and De, Di | <input type="radio"/> |
| | c) if two spring forces and the spring lengths are specified | | | L0, n and d | <input type="radio"/> |
| | | | | L0, n and De, Di | <input type="radio"/> |
| 12 | Set Test Springs ! Supply remaining springs set <input type="radio"/> not set <input type="radio"/> | | | | |
| | Springs to be supplied not set may be longer than L0 | | | | |

Copying of this document and giving it to other and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

| | | | | | |
|-------|--------------|------|------|--------------------|------|
| | | | | Date | Name |
| | | | | Compl. | |
| | | | | Check | |
| | | | | Stand. | |
| | | | | | |
| Cond. | Modification | Date | Name | ZILLER Böhmenkirch | |

Feder

D-04024