




1	No. of Active Coils	n = 3.5
	Total No. of Coils	nt = 5.5
2	Direction of Coils	right ☒ left ☐
3	Deburring of Spring Ends	no ☒ inside ☐ outside ☐
4	Working Path (Stroke)	
5	Stress Cycle Frequency	
6	Range of working temperature	0 .. 80 °C
7	Wire or Rod Surface	drawn ☒ rolled ☐ tipless grinding ☐ spring shot-blasted with steel balls ☐
8	Surface Protection:	
9	Material: 1.4310	

10	Permissible Deviations according to EN 15800 Quality Class				DIN 2096
	1	2	3		
De, Di	☐	☐	☐		☐
L0	☐	☐	☐		☐
F1	☐	☐	☐		☐
F2	☐	☐	☐		☐
e1	☐	☐	☐		☐
e2	☐	☐	☐		☐
d					
11	Manufacturing Tolerance			by:	
	a) if the spring force and the spring length are specified			L0	☐
	b) if the spring force, the spring length and L0 are specified			n and d	☒
				n and De, Di	☐
	c) if two spring forces and the spring lengths are specified			L0, n and d	☐
				L0, n and De, Di	☐
12	Set Test Springs ! Supply remaining springs set ☐ not set ☐				
	Springs to be supplied not set may be longer than L0				

				Date	Name	Feder
				Compl.		
				Check		
				Stand.		
						RD-01011
Cond.	Modification	Date	Name	ZILLER Böhmenkirch		



Copying of this document and giving it to other and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.